



# **CRACKFILL**<sup>™</sup> **PASTE**

## **READY TO USE FIBRE REINFORCED ACRYLIC POLYMER BASED CRACK FILLING PASTE**

### **BENEFITS**

- Ready to use.
- Excellent thixotropicness.
- Excellent adhesion.
- Easy to apply.
- Excellent finishing.
- Can be used on all common type of building interiors and exteriors.
- Dense and cohesive paste will not allow water penetration.
- High performance non structural crack filling paste.
- Allow surface to breath.
- Resistance to weather and chemical.
- Safe to use.
- Non toxic.
- Available in attractive white colour.

### **PRODUCT**

**CRACKFILL PASTE** is an easy to use, acrylic polymer based crack filling paste, which ensures fibre reinforced perfect filling of cracks and will not allow water penetration.

### **APPLICATION**

**Surface Preparation** : Chip out the crack in 'V' groove and clean all the debris and loose particles. Prewet the surface. The prepared surface should be free from oil, grease, dust, dirt etc.

**Application** : To obtain a smooth surface, use a flat tool, like a steel spatula to apply the material into the cracks.

### **PACKING & COVERAGE**

**CRACKFILL PASTE** is available in 1kg, 5kg, 10kg and 20kg. plastic bucket. 1kg of **CRACKFILL PASTE** will approximately cover 7 to 8 running meter having the width and depth of 3mm to 4mm.

### **SHELF LIFE & STORAGE**

**CRACKFILL PASTE** will have a shelf life of **12 months** in unopened containers when kept in dry conditions at a temperature between 5°C to 35°C. Material must be kept under shaded area and away from direct sunlight. Storage at higher temperature or high humidity may reduce shelf life.

### **HEALTH & SAFETY**

**CRACKFILL PASTE** is non-hazardous. However inhalation of dust should be avoided while handling. In wet state if contact with eye occurs, wash well with plenty of clean water.

### **SPECIFICATION**

**CRACKFILL PASTE** is an acrylic polymer based crack filling paste available in 1kg, 5kg, 10kg and 20kg plastic bucket. 1kg of **CRACKFILL PASTE** will approximately cover 7 to 8 running meter having the width and depth of 3mm to 4mm.

# CRACKFILL™ PASTE



## QUALITY ASSURANCE

Fairmate manufactures entire range of construction chemicals under compliance of ISO 9001, ISO 14001 & ISO 45001 (Occupational Health and Safety) certified by ISOQAR/UK.

## TECHNICAL SERVICES

While new advances and changes will take place but one thing will never change is quality and meeting special needs of our customers. Our quality control laboratory and technical experts are available to provide additional information and technical assistance. We are eager to work with you in development of new product and resolve your problem.

## OUR RANGE OF PRODUCTS

<b>CONCRETE ADMIXTURES</b> <b>WATERPROOFING SYSTEMS</b> <b>ENGINEERING GROUTS</b> <b>INDUSTRIAL FLOOR SURFACES</b>	<b>CONCRETE REPAIRS</b> <b>SURFACE TREATMENT</b> <b>PREPACKED CONCRETE MORTAR</b> <b>PROTECTIVE COATING</b>	<b>HIGHWAY REPAIR</b> <b>ARCHITECTURAL FINISH</b>
---	--	--

"Contact us to discuss any potential requirement and you will be assured of a rapid and effective response - that's guarantee !!"

Complete range of construction chemical products - Foundation to Finish



**Corporate Office**  
**FAIRMATE CHEMICALS PVT. LTD.**  
8, "SAI SUDHA", Arunoday Society,  
Alkapuri, Vadodara 390 007. Gujarat, India

In technical collaboration with RBP Ltd. UK  
**Always better than the best in Quality, Services & Values**

☎ +91 265 2330803, 2331193  
✉ sales@fairmate.com  
📞 **1800 12345 34** (Toll Free) 🌐 www.fairmate.com



### International Manufacturing Hubs / Offices:

AUSTRALIA BANGLADESH BHUTAN BRAZIL ESTONIA INDONESIA KENYA MYANMAR NEPAL PHILIPPINES QATAR RUSSIA SRI LANKA USA VENEZUELA

The information given in this data sheet is based on both the current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we cannot accept the responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. The user of the product must test the product's suitability for the intended application and purpose. In view of the continuing research and development being undertaken in our laboratories. Fairmate reserves the right to change the properties of its products. We advise customers in their own interest to ensure that this data sheet has not been superseded by a more up-to-date publication. All products are sold subjected to our standard conditions of sale which are available on request. Field services, where provided, does not constitute supervisory responsibility. For additional information, please contact our local FAIRMATE representative.